



250L Flammable Liquids Storage Cabinet

Class 3 Liquids

Standard Features:

- Double walled sheet steel construction with a 40mm thermic air barrier
- High capacity liquid tight sump to contain spills - 150mm deep
- Self-closing, close fitting doors that latch at 2 points
- Built in flash arrestors and vent openings [for mechanical ventilation systems]
- Strong fully adjustable shelving perforated for free air movement, 100mm adjustment increments
- Sequential door closing system
- Stainless steel pin with continuous hinging for strength and reliability
- State of the art powder coat finish for high durability and performance
- Distinct safety signs and directions that comply with AS 1216 and AS 1319
 - 1. Each cabinet is marked with the name and address of the manufacturer
 - 2. The maximum storage capacity
 - 3. A Class 3 dangerous goods label with sides of at least 250mm nominal.
 - 4. A sign bearing the words 'NO SMOKING, NO IGNITION SOURCES WITHIN 3M'.
- Designed and Manufactured in full conformance to AS 1940:2017 The storage and handling of flammable and combustible liquids



Specifications:

Dimensions (mm)				Storage Levels	
	H	W	D		
External	1825	1100	500	Sump Capacity (L)	64
Internal	1570	980	400	Weight (kg)	180
				Max Capacity (L)	250
				Complies With	AS1940 - 2017

Winchester Size			Drum Size			
0.5 L	2.5 L	5 L	4 L	20 L	60 L	205 L
ø 65mm	ø 135mm	ø 190mm	ø 180mm	ø 300mm	ø 400mm	ø 600mm
450*	63	30	50*	9*	4	0

*5 storage levels

